

## GHS SAFETY DATA SHEET (SDS)

### SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

**Product:** PA0828

**PTM & W INDUSTRIES, INC.**                      **PHONE NUMBER: (562) 946-4511**  
**10640 S. PAINTER AVE.**                      **CHEMICAL TRANSPORTATION EMERGENCY:**  
**SANTA FE SPRINGS, CA. 90670-4092**                      **CHEMTREC (800) 424-9300**

**DATE OF PREPARATION:** 4/27/2015    **SUPERSEDES:** 5/12/2014

**Product Type:** Mold Release

**Product Use:** Industrial Mold Release supplied exclusively for workplace use.

**Signal Word:** Danger

**Hazard Label(s):**

Flammable    Health    Irritant    Environment



**Hazard statement(s):**

**H225:** Highly flammable liquid and vapour.

**H304:** May be fatal if swallowed and enters airways.

**H315:** Causes skin irritation.

**H320:** Causes eye irritation.

**H361:** Suspected of damaging fertility or the unborn child.

**H373:** May cause damage to organs through prolonged or repeated exposure.

(Refer to Section 16 for Hazard Classifications.)

**Precautionary statement(s):**

**P202:** Do not handle until all safety precautions have been read and understood

**P210:** Keep away from heat/sparks/open flames/hot surfaces – No smoking.

**P261:** Avoid breathing dust/fume/gas/mist/vapours/spray.

**P270:** Do not eat, drink or smoke when using this product.

**P281:** Use personal protective equipment as required.

**P285:** In case of inadequate ventilation wear respiratory protection.

**P273:** Avoid release to the environment.

### SECTION 2 — HAZARD(S) IDENTIFICATION

NO.	CANCER	REPRO-TOX	TARGET ORGANS	ACGIH/TLV	OSHA/PEL
1	NO	NO	LUNG, KIDNEY, CNS	50 ppm	500 ppm
2	NO	NO	LUNG, KIDNEY, CNS	50 ppm	500 ppm
3	NO	NO	LUNG, KIDNEY, CNS	50 ppm	300 ppm
4	NO	NO	LUNG, KIDNEY, CNS	100 ppm	100 ppm
6	NO	NO	LUNG, KIDNEY, CNS	100 ppm	100 ppm

PA0828 SDS #1204

Page 1

### SECTION 3 — COMPOSITION / INFORMATION ON INGREDIENTS

UNDER GHS-OSHA §4.11 THE PRECISE COMPOSITION OF THIS PRODUCT IS WITHHELD AS CONFIDENTIAL BUSINESS INFORMATION (CBI). A MORE COMPLETE DISCLOSURE CAN BE PROVIDED TO A HEALTH, OR SAFETY PROFESSIONAL WHEN NECESSARY.

**Substance/Mixture:** Mixture

NO.	COMPONENT	CAS. NO.	PERCENT
1	NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-49-0	< 100%
2	n-HEXANE	110-54-3	< 50%
3	CYCLOHEXANE	110-82-7	< 10%
4	STODDARD SOLVENT	8052-41-3	< 2.5%
5	TRIMETHYLSILICA	68988-56-7	< 2.2%
6	XYLENE	1330-20-7	< 0.8%
7	PSUEDOCUMENE	95-63-6	< 0.1%

### SECTION 4 — FIRST-AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES:

- **EYES:** IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.
- **SKIN:** WASH AFFECTED AREA IMMEDIATELY WITH LARGE AMOUNTS OF SOAP AND WATER. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE. CONTACT A PHYSICIAN IF IRRITATION OCCURS.
- **INHALATION:** REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION.
- **INGESTION:** DO NOT INDUCE VOMITING. GIVE LARGE QUANTITIES OF WATER. CALL A PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

### SECTION 5 — FIRE-FIGHTING MEASURES

FLASH POINT: -25°F (FOR PRODUCT OR LOWEST FLASH POINT INGREDIENT)

FLAMMABILITY CLASSIFICATION: EXTREMELY FLAMMABLE CLASS (IA)

EXTINGUISHING MEDIA: WATER FOG, DRY CHEMICAL, CARBON DIOXIDE, OR FOAM.

**NOTE:** EITHER ATMOSPHERE-SUPPLY OR AIR-PURIFYING RESPIRATORS SHOULD BE AVAILABLE FOR FIRE FIGHTERS (20 CFR 1910.134).

### SECTION 6 — ACCIDENTAL RELEASE MEASURES

- **IF MATERIAL IS SPILLED:** AVOID CONTACT WITH MATERIAL. PERSONS NOT WEARING PROPER PROTECTIVE EQUIPMENT (SEE BELOW) SHOULD BE EXCLUDED FROM THE AREA UNTIL CLEAN UP IS COMPLETE. DIKE AREA TO PREVENT SPILL SPREADING AND SCOOP UP EXCESS TO RECOVERY CONTAINERS. ABSORB REMNANT ON NONCOMBUSTIBLE MATERIAL SUCH AS CLAY AND SHOVEL INTO CONTAINERS FOR DISPOSAL.
- **WASTE DISPOSAL METHOD:** DISPOSE OF ANY WASTE(S) GENERATED ABOVE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

Page 2

## SECTION 7 — HANDLING AND STORAGE

- AVOID SKIN AND EYE CONTACT.
- AVOID BREATHING VAPOR, MIST OR FUMES.
- ENSURE THAT ALL CONTAINERS ARE PROPERLY LABELED TO PREVENT ACCIDENTAL INGESTION OR IMPROPER DISPOSAL.
- RESEAL PARTLY USED CONTAINERS.
- WASH WITH SOAP AND WATER BEFORE EATING, DRINKING OR USING TOILET FACILITIES.
- STORE UNDER COOL, DRY CONDITIONS AND AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES.
- OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORKING PRACTICE.

## SECTION 8 — EXPOSURE CONTROLS/ PERSONAL PROTECTION

- **RESPIRATORY PROTECTION:** NOT NORMALLY NECESSARY UNLESS THE MATERIAL IS BEING USED IN SUCH A WAY AS TO PRODUCE DUST, MIST, VAPOR, FUMES, OR SMOKE, IN WHICH CASE NIOSH APPROVED RESPIRATORY PROTECTION SHOULD BE USED.
- **VENTILATION:** SHOULD BE SUFFICIENT TO CONTROL ANY DUST, MIST, VAPOR OR FUMES PRODUCED BY PROCESSING OR HANDLING METHOD. BREATHING OF VAPOR MUST BE AVOIDED.
- **HAND PROTECTION:** IMPERVIOUS GLOVES, NEOPRENE OR NITRILE RUBBER GLOVES.
- **EYE PROTECTION:** SPLASH PROOF GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS.
- **OTHER PROTECTIVE EQUIPMENT:** CLEAN, BODY COVERING CLOTHING AND FOOTWEAR.

## SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

- PHYSICAL STATE.....: LIQUID
- ODOR.....: HYDROCARBON
- COLOR.....: CLEAR OR BLUE
- pH.....: NEUTRAL
- SP. GR.....: 0.70
- DENSITY.....: 5.8 lbs. / gal.
- VAPOR PRESSURE.....: N.A.

NOTE: OTHER PROPERTIES ARE EITHER NOT AVAILABLE, OR DO NOT APPLY.

## SECTION 10 — STABILITY AND REACTIVITY

- **STABILITY:** STABLE UNDER NORMAL STORAGE CONDITIONS. UNSTABLE AT ELEVATED TEMPERATURES.
- **INCOMPATIBILITY:** STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS, AND STRONG MINERAL AND ORGANIC BASES.
- **HAZARDOUS DECOMPOSITION PRODUCTS:** OXIDES OF CARBON, AND OTHER UNKNOWN ORGANIC COMPOUNDS.

## SECTION 11 — TOXICOLOGICAL INFORMATION

### EFFECTS OF OVEREXPOSURE:

#### ACUTE:

- **EYES:** LIQUID, VAPORS AND MIST ARE IRRITATING AND CAN CAUSE A STINGING SENSATION, TEARING, REDDENING AND SWELLING OF THE EYES.
- **SKIN:** MODERATELY IRRITATING, & MAY CAUSE SKIN DEFATTING OR SENSITIZATION.
- **INHALATION:** CAN CAUSE NASAL AND RESPIRATORY IRRITATION, CNS EFFECTS INCLUDING FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS, AND EVEN DEATH.
- **INGESTION:** CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE FATAL CHEMICAL PNEUMONITIS.

#### CHRONIC:

- EXPOSURE MAY DAMAGE PERIPHERAL NERVE TISSUE & RESULT IN PERIPHERAL NEUROPATHY. MAY CAUSE KIDNEY DAMAGE OR CNS EFFECTS. PREEXISTING DISORDERS MAY ALSO BE AGGRAVATED BY EXPOSURE.

## SECTION 12 — ECOLOGICAL INFORMATION

### ECOTOXICITY EFFECTS:

- **AQUATIC TOXICITY:** NO DATA IS AVAILABLE ON THE PRODUCT ITSELF.
- **TOXICITY TO OTHER ORGANISMS:** NO DATA AVAILABLE.

### PERSISTENCE AND DEGRADABILITY:

- **MOBILITY:** NO DATA IS AVAILABLE ON THE PRODUCT ITSELF.
- **BIOACCUMULATION:** NO DATA IS AVAILABLE ON THE PRODUCT ITSELF.

## SECTION 13 — DISPOSAL CONSIDERATIONS

- **WASTE DISPOSAL METHOD:** DISPOSE OF WASTE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS.
- **CONTAINER DISPOSAL:** SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUE, ALL LABELED HAZARD PRECAUTIONS MUST BE OBSERVED. CONSULT WITH FEDERAL, STATE, AND LOCAL AUTHORITIES FOR DEFINITIONS OF "EMPTY" AND PROPER DISPOSAL PRACTICES.

## SECTION 14 — TRANSPORT INFORMATION

### • U.S. Department of Transportation Ground (49 CFR)

UN NUMBER.....: UN1866  
PROPER SHIPPING NAME.....: RESIN SOLUTION  
CONTAINS.....: NAPHTHA, LIGHT ALIPHATIC  
HAZARD CLASS.....: 3  
PACKAGING GROUP.....: III

### • International Air Transportation (ICAO/IATA)

UN NUMBER.....: UN1866  
PROPER SHIPPING NAME.....: RESIN SOLUTION  
CONTAINS.....: NAPHTHA, LIGHT ALIPHATIC  
HAZARD CLASS.....: 3  
PACKAGING GROUP.....: III

### • Water Transportation (IMO/IMDG)

UN NUMBER.....: UN1866  
PROPER SHIPPING NAME.....: RESIN SOLUTION  
CONTAINS.....: NAPHTHA, LIGHT ALIPHATIC  
HAZARD CLASS.....: 3  
PACKAGING GROUP.....: III  
MARINE POLLUTANT.....: YES

## SECTION 15 — REGULATORY INFORMATION

### A. CAL SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT OF 1986

NO.	CHEMICAL NAME	CAS. NO.	CANCER/REPRO.TOX	QUANTITY
*	ETHYL BENZENE	100-41-4	YES NO	<0.5%
*	NAPHTHALENE	91-20-3	YES NO	<0.1%
*	BENZENE	71-43-2	YES YES	<0.09%
*	TOLUENE	108-88-3	NO YES	<0.0003%

THIS PRODUCT MAY CONTAIN TRACES OF OTHER PROP. 65 LISTED CHEMICALS AS IMPURITIES. HOWEVER, ANY USED AS INGREDIENTS ARE LISTED ABOVE.

### B. CERCLA — §40 CFR 302.4

RELEASES EXCEEDING THE REPORTABLE QUANTITY (RQ) MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER. (800)424-8802  
RQ FOR THIS PRODUCT IS 9,434 LBS. WHEN BASED ON ITS' (CAS 64742-49-0) CONTENT. (CAS 64742-49-0) CAN ALSO BE CLASSIFIED AS AN "OIL" AND SO RELEASES MAY FALL UNDER THE CERCLA PETROLEUM EXCLUSION AS NOT REPORTABLE.

### C. RCRA — §40 CFR 261.33

PRODUCT IS A D001 IGNITABLE LIQUID WASTE. THE BDAT IS INCINERATION, FUELS SUBSTITUTION, OR RECOVERY. NO. 2 AND NO. 3 ARE RCRA U056 HAZARDOUS WASTE.

### D. SARA TITLE III — §52 CFR 13378, §52 CFR 21152

NO.	RQ (lbs.) (•1)	TPQ (lbs.) (•2)	SEC.313 (•3)	313 CAT. (•4)	311/312 (•5)
2	NONE	NOT LISTED	YES	NONE	H1, H2, P3
3	NONE	NOT LISTED	YES	NONE	H1, H2, P3

- 1 = REPORTABLE QUANTITY OF EXTREMELY HAZARDOUS SUBSTANCE, SEC. 302
- 2 = THRESHOLD PLANNING QUANTITY, EXTREMELY HAZARDOUS SUBSTANCE, SEC. 302
- 3 = TOXIC CHEMICAL, SEC. 313 (INDIVIDUAL CHEMICAL LISTED)
- 4 = TOXIC RELEASE INVENTORY FORM CATEGORY SEC. 313 (40 CFR 372.65 C)
- 5 = HAZARD CATEGORY FOR SARA SEC. 311/312 REPORTING
- H1 = IMMEDIATE (ACUTE) HEALTH HAZARD H2 = DELAYED (CHRONIC) HEALTH HAZARD
- P3 = FIRE HAZARD P4 = SUDDEN PRESSURE RELEASE HAZARD P5 = REACTIVE HAZ.

### E. VOC — SCAQMD RULES

NO.	CHEMICAL	QUANTITY	VP mm Hg	gms./l. @ 20°C
1	NAPHTHA, LIGHT ALIPHATIC	< 89%	125	623
4	STODDARD SOLVENT	< 2.5%	2	20
6	XYLENE	< 1.0%	5.1	9

### F. INTERNATIONAL CHEMICAL INVENTORY STATUS:

EINECS-EU	Listed, Exempted, Polymer substance, or as no longer polymer.
AICS-AUSTRALIA	All components are listed or exempted.
ENCS-JAPAN	All components are listed or exempted.
ISHL-JAPAN	All components are listed or exempted.
KECI/ECL-KOREA	All components are listed or exempted.
IECSC/SEPA-CHINA	All components are listed or exempted.
PICCS-PHILIPPINES	All components are listed or exempted.
DSL-CANADA	All components are listed or exempted.
TSCA-USA	All components are listed or exempted.

### G. WHMIS (CANADA):

- WHMIS: D2B Materials Causing Other Toxic Effects –Toxic Material
- WHMIS: B2 Flammable Liquids – Flashpoint of < 37.8°C (100°F)

## SECTION 16 — OTHER INFORMATION

#### HMIS III CODES:

HEALTH .....= **2**  
FLAMMABILITY .....= **3**  
REACTIVITY .....= **0**

#### RATINGS:

0 = MINIMAL 3 = SERIOUS  
1 = SLIGHT 4 = SEVERE  
2 = MODERATE

⇒ PERSONAL PROTECTION RATING TO BE SUPPLIED BY USER DEPENDING ON CONDITIONS OF USE.

#### Hazard Classifications:

- H225:** Highly flammable liquid and vapour. (Flam. Liq. 2)
- H304:** May be fatal if swallowed and enters airways. (Asp. Tox. 1)
- H315:** Causes skin irritation. (Skin Irrit. 2)
- H320:** Causes eye irritation. (Eye Irrit. 2B)
- H361:** Suspected of damaging fertility or the unborn child. (Repr. 2)
- H373:** May cause damage to organs through prolonged or repeated exposure. (STOT RE2)

DATE OF PREPARATION: 4/27/2015 SUPERSEDES: 5/12/2014

We believe that the information contained herein is correct as of the date of this Safety Data Sheet. Since the use of this information and these opinions and the conditions of use of this product are not within the control of PTM & W, it is the user's obligation to determine the conditions of safe use of the product.

PTM & W makes no warranty, expressed or implied regarding the accuracy of these data. PTM & W assumes no responsibility for injury from the use of the product described herein. Further, there are many international, federal, state, and local laws and regulations governing chemical products and as it is beyond the scope of this SDS to determine which of these apply, it is the responsibility of the user to determine how these affect their use of the product.

PTM&W assumes no obligation or liability for the information given, or results obtained, all such being given and accepted at users' risk.

Alteration of this document is strictly prohibited.

— END OF SDS —

Copyright 2015 PTM&W Industries, All rights reserved.